

Instructions Satin Finishing Wax

How to Apply General Finishes Satin Wax

General Finishes Satin Wax Application Steps

Light Polishing:

1. Shake container well.
2. Wipe on a thin, even coat with a clean cloth.
3. Let sit 10 minutes.
4. Polish with a soft cloth, wiping away the excess in the direction of the wood grain.

Buffing A Topcoat to A High Gloss:

1. Shake container well.
2. Wipe on a thin, even coat with a clean cloth.
3. Let sit 1-2 minutes.
4. Buff off excess with a buffing or sanding pad (see below) in the direction of the wood grain. The higher/finer grit you use, the easier it will be to achieve a high-gloss finish.
5. Buffing Tools:
 1. Norton Abrasives, Yellow Block
 - 1000-grit, 1500-grit, 2000-grit
 - Creates a high-gloss finish
 2. Klingspor Fusion Pads
 - 2800- to 3500-grit
 - Ideal for painted and gloss finishes
 3. Klingspor Superfine Sanding Pad
 - 220-grit
 - General purpose option for rubbing out topcoats and paints with a flat or satin sheen
 4. Merka Mirlon Pads
 - Total 1500 (gray)
 - Total 2500 (gold)
 - Ideal for oil-based finishes or between coats of paint

Fixing A Scratch:

1. Shake container well.
2. Do not sand "dry-on-dry" to remove scratch marks.

Instructions Satin Finishing Wax

3. Add Satin Wax as a lubricant on the pad AND on the surface of your project, then spread smooth with a rag.
4. Let sit 10 minutes.
5. Polish with a soft cloth, wiping away the excess in the direction of the wood grain.

Storage of Maintenance Products

Life of Product

Maintenance products are best used within 1 year of the manufacture date listed on the bottom of the can. The following best practice will increase the life of your product:

Store in moderate temperatures. Avoid temperatures above 80°F/26°C. Heat-damaged product cannot be revitalized. Temperature-controlled spaces, such as a basement, are ideal for storage. Do not store product in an attic, garage, in direct sunlight, or next appliances with heat or flame such as a furnace.

Warnings and Warranties

Compatibility

Do not use water-based products with Linseed Oils or Danish Oils.

Limited Warranty

General Finishes products must be tested to your complete satisfaction before using. General Finishes will not be responsible for color satisfaction, misapplication, nor compatibility with other manufacturers' products. General Finishes will be responsible only for the cost of our products, and not for costs such as labor, damage, or project replacement.

Contamination and Compatibility

Our finishes are engineered as a system and are compatible with each other. General Finishes cannot guarantee an ideal refinish when applying our products on top of or combined with another company's products or over surfaces that have been in contact with waxes, polishes or sprays containing contaminants such as silicone. Test for adherence and aesthetics before beginning.

Warning

If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log onto www.epa.gov/lead.

FIRST AID:

Seek immediate medical attention if symptoms occur due to the following. **EYE CONTACT:** Remove any contact lenses. Flush eyes with water for 20+ minutes while lifting upper and lower eyelids. **SKIN CONTACT:** Wash thoroughly after handling. **INHALATION:** Move to fresh air and loosen clothing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. **INGESTION:** Call physician immediately. Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

Warning

This product contains a chemical known to the State of California to cause cancer and birth defects. Do not swallow; first aid: drink water to dilute product. May cause eye or skin irritation; first aid: flush eyes

Instructions Satin Finishing Wax

thoroughly with water.

Warning

Keep out of reach of children. Avoid contact with eyes. Keep container tightly closed when not in use. Wash thoroughly after handling.